

Amendments to the Claims

Please amend Claims 10-12. The Claim Listing below will replace all prior versions of the claims in the application:

Claim Listing

1. (Previously presented) A method implemented in an Internet node for reducing Internet bandwidth used for VoIP modem relay, a first modem coupled to the Internet node and a second modem coupled to an other Internet node, the method comprising:

upon detecting no data packets received at the Internet node from the other Internet node over an IP network to transmit over a switched telephone network to the first modem, regenerating idle data at the Internet node to transmit to the first modem, the regenerated idle data used to maintain a connection between the first modem and the second modem; and

upon detecting idle data received from the first modem over a switched telephone network at the Internet node to forward to the other Internet node over the IP network in a payload of a data packet, suspending transmission of data packets to the other Internet node for transmission to the second modem; and resuming transmission of data packets to the other Internet node for transmission to the second modem, upon receiving data from the first modem that is not idle data.

2. (Original) The method as claimed in Claim 1 wherein the idle data is 'FF'.

3. (Original) The method as claimed in Claim 1 wherein the idle data is '7E'.

4. (Original) The method as claimed in Claim 1 wherein the Internet node is an Internet Gateway.

5. (Previously presented) An apparatus at an Internet node for reducing Internet bandwidth used for transferring data between a first modem and a second modem over an IP network, the apparatus comprising:

means for detecting idle data received from the first modem over a switched telephone network to forward over the IP network;

means for suspending transmission of data packets to an other Internet node for transmission to the second modem upon detecting idle data received from the first modem;

means for resuming transmission of data packets to the other Internet node for transmission to the second modem, upon receiving data from the first modem that is not idle data; and

means for regenerating idle data to transmit to the second modem upon detecting no data packets received over the IP network to forward to the second modem, to maintain a connection between the first modem and the second modem.

6. (Original) The apparatus as claimed in Claim 5 wherein the idle data is 'FF'.
7. (Original) The apparatus as claimed in Claim 5 wherein the idle data is '7E'.
8. (Original) The apparatus as claimed in Claim 5 wherein the Internet node is an Internet gateway.
9. (Previously presented) A computer readable storage medium containing instruction readable by computer to configure the computer to perform a method for controlling an Internet node comprising:

an idle detect module which detects idle data received from a first modem coupled to the Internet node over a switched telephone network to be forwarded to a second modem over an IP network in a payload of a data packet, suspends transmission of data packets to an other Internet node for transmission to the second modem upon detecting idle data received from the first modem and resumes transmission of data packets to the other Internet node for transmission to the second modem upon receiving data from the first modem that is not idle data; and

an idle generate module which regenerates idle data to transmit to the first modem upon detecting no data packets received from the other Internet node over the IP network from a second modem coupled to the other Internet node to be forwarded to the first modem, the regenerated idle data used to maintain a connection between the first modem and the second modem.

10. (Currently Amended) The computer readable storage medium ~~Internet node~~ as claimed in Claim 9 wherein the idle data is 'FF'.

11. (Currently Amended) The computer readable storage medium ~~Internet node~~ as claimed in Claim 9 wherein the idle data is '7E'.

12. (Currently Amended) The computer readable storage medium ~~Internet node~~ as claimed in Claim 9 wherein the Internet node is an Internet gateway.

13. (Previously presented) A computer program product, for reducing Internet bandwidth used for transferring data between a first modem and a second modem over an IP network, the first modem coupled to a first Internet node, the second modem coupled to a second Internet node, the first Internet node and the second Internet node coupled to the IP network, the computer program product comprising a computer usable medium having computer readable program code thereon, including program code which:

regenerates idle data in the first Internet node to transmit to the first modem, upon detecting no data packets received from the second Internet node over the IP network to forward to the first modem; and

detects idle data received from the first modem over a switched telephone network at the first Internet node to forward to the second Internet node over the IP network in a payload of a data packet, the regenerated idle data used to maintain the connection between the first modem and the second modem;

suspends transmission of data packets to the second Internet node for transmission to the second modem upon detecting idle data received from the first modem; and

resumes transmission of data packets to the second Internet node for transmission to the second modem upon receiving data from the first modem that is not idle data.

14. (Cancelled)

15. (Cancelled)

16. (Previously presented) The method of claim 1, wherein the idle data transmitted over the switched telephone network is encoded in a PCM stream.

17. (Previously presented) The method of claim 1 further comprising:

establishing a modem connection between the first modem and the second modem.